

ТУ 1469-002-05777029-2006

Таблица 1 – Основные размеры и коэффициент несущей способности тройников сварных

Наружный диаметр магистрали Dн, мм	Размеры											
	325	377	426	530	630	720	820	1020	1067	1220	L	H
530	1,55										325	515
		1,58									375	515
			1,60								425	515
				1,64							530	530
630	1,52										325	565
		1,55									375	565
			1,57								425	565
				1,61							530	580
					1,64						630	630
720	1,47										325	610
		1,52									375	610
			1,55								425	610
				1,58							530	625
					1,62						630	675
						1,64					720	720
820	1,42										325	660
		1,48									375	660
			1,52								425	660
				1,56							530	675
					1,59						630	725
						1,62					720	770
							1,64				820	820

1020	1,32										325	760
		1,39									375	760
			1,44								425	760
				1,52							530	775
					1,55						630	825
						1,58					720	870
							1,60				820	920
								1,64			1020	1020
1067	1,30										325	785
		1,37									375	785
			1,43								425	785
				1,51							530	800
					1,55						630	850
						1,57					720	900
							1,59				820	950
								1,63			1020	1050
								1,64		1070	1070	
1220	1,23										325	860
		1,30									375	860
			1,36								425	860
				1,46							530	875
					1,52						630	925
						1,55					720	970
							1,57				820	1020
								1,61			1020	1120
									1,62		1070	1150
									1,64	1220	1220	